

REFERENCE PART NUMBER 000020306E05

<SC> :SIGNIFICANT CHARACTERISTICS ▽:CRITICAL CHARACTERISTICS									
BREAK SHARP CORNERS MAY BE EITHER A CHAMFER OR A RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.							MAHINDRA & MAHINDRA LIMITED TRACTOR DIVISION KANDIVLI (EAST), MUMBAI 400 101, INDIA.		
UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989									
DIMENSIONS									
LINEAR IN mm.	OVER	0.5	3	6	30	120	400	1000	2000
	UPTO	3	6	30	120	400	1000	2000	4000
f FINE (X.XXX)		± 0.05	± 0.05	± 0.1	± 0.15	± 0.2	± 0.3	± 0.5	-
m MEDIUM (X.XX)		± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2
c COARSE (X.X)		± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2	± 3	± 4
v VERY COARSE (X)		-	± 0.5	± 1	± 1.5	± 2.5	± 4	± 6	± 8
ANGULAR IN deg.	LENGTH OF SHORTER SIDE OF THE ANGLE IN mm.								
	OVER	-	10	50	120	400			
	UPTO	10	50	120	400	-			
f FINE (X.XXX)		± 1°	± 0° 30'	± 0° 20'	± 0° 10'	± 0° 5'			
m MEDIUM (X.XX)									
c COARSE (X.X)		± 1° 30'	± 1°	± 0° 30'	± 0° 15'	± 0° 10'			
v VERY COARSE (X)		± 3°	± 2°	± 1°	± 0° 30'	± 0° 20'			
PART OF THIS DRAWING / DOCUMENT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN PERMISSION OF M & M LTD.									
COMPUTER GENERATED DRAWING					DO NOT CHANGE MANUALLY				
IF IN DOUBT, ASK			DO NOT SCALE		DRG SIZE :		ALL DIMENSIONS ARE IN mm.		
							CHECK DRG WITH LATEST CHANGE No		
E.R.NO.		LET	LOC	REVISIONS		DSNR	CKR.	APPR.	DATE

ER23I0000004		AB	-	NOTE UPDATED		PRP	NVC	DS	04-07-24
E.R.NO.		LET	LOC	REVISIONS		DSNR	CKR.	APPR.	DATE

NAME		SIGN	DATE	FIRST USED TRCR. MODEL
CAD ENGG.				
DESIGNER				SCALE
CHECKER				SHEET OF
APPR.BY				UNIT QTY. :
				WEIGHT : kg.